

# 400

400 SERIES SKID STEERS

**CASE**  
PROFESSIONAL PARTNER



## COMPACT RANGE



MODEL	410	420	430	440
Engine	49 net hp (37 kW)	56 net hp (42 kW)	74 net hp (55.2 kW)	82 net hp (61.1 kW)
Engine type	Case 422/M2 naturally aspirated, 4-cylinder diesel engine	Case 422T/M2 turbocharged, 4-cylinder diesel engine	Case Family III, 445/M2 naturally aspirated, 4-cylinder diesel engine	Case Family III, 445T/M2 turbocharged, 4-cylinder diesel engine
Loader geometry	Radial	Radial	Radial	Radial
Operating load	1,500 lb (681 kg)	1,750 lb (794 kg)	2,000 lb (908 kg)	2,200 lb (998 kg)
Bucket breakout force	4,129 lbf (18 367 N)	4,129 lbf (18 367 N)	5,413 lbf (24 079 N)	6,198 lbf (27 571 N)
Bucket hinge pin height	114.6 in (2.91 m)	114.6 in (2.91 m)	121.5 in (3.09 m)	121.5 in (3.09 m)
Reach	23.6 in (0.60 m)	23.6 in (0.60 m)	21.3 in (0.54 m)	21.3 in (0.54 m)
Wheelbase	41.2 in (1.05 m)	41.2 in (1.05 m)	43.1 in (1.10 m)	43.1 in (1.10 m)
Drive chains (#)	80	80	100	100
Minimum bucket width	60 in (1.5 m)	60 in (1.5 m)	66 in (1.6 m)	66 in (1.6 m)
Operating weight	5,483 lb (2488 kg)	5,813 lb (2637 kg)	6,875 lb (3119 kg)	6,980 lb (3167 kg)

### OPTIONS

Hydraulic self-leveling	Yes	Yes	Yes	Yes
Ride control	Yes	Yes	Yes	Yes
High-flow hydraulics	No	Yes	Yes	Yes
Air conditioning	No	No	Yes	Yes
2-speed	No	No	Yes	Yes



### AT-A-GLANCE

- Heavy-duty design for long life and low cost of operation
- Case large displacement high torque Tier II Certified Engines for maximum productivity
- Easy Tilt ROPS/Cab for fast and easy maintenance
- Comfortable, low-effort servo-hydrostatic controls for operator comfort



# HEAVY RANGE



MODEL	435	445	450	465
Engine	72 net hp (54 kW)	74 net hp (55.2 kW)	82 net hp (61.2 kW)	82 net hp (61.2 kW)
Engine type	Case Family III 334T/M2 turbocharged, 3-cylinder diesel engine	Case Family III 445/M2 naturally aspirated, 4-cylinder diesel engine	Case Family III 445T/M2 turbocharged, 4-cylinder diesel engine	Case Family III 445T/M2 turbocharged, 4-cylinder diesel engine
Loader geometry	Vertical	Vertical	Radial	Vertical
Operating load	2,300 lb (1043 kg)	2,500 lb (1134 kg)	2,450 lb (1111 kg)	3,000 lb (1364 kg)
Bucket breakout force	6,000 lbf (26 688 N)	6,000 lbf (26 688 N)	6,200 lbf (27 578 N)	6,175 lbf (27 468 N)
Bucket hinge pin height	120 in (3.04 m)	120 in (3.04 m)	124.5 in (3.16 m)	125.5 in (3.19 m)
Reach	29.9 in (0.76 m)	33.7 in (0.86 m)	26.7 in (0.68 m)	36.8 in (0.935 m)
Wheelbase	44.9 in (1.14 m)	44.9 in (1.14 m)	46.0 in (1.17 m)	50.6 in (1.28 m)
Drive chains (#)	100	100	120	120
Minimum bucket width	73 in (1.9 m)	73 in (1.9 m)	73 in (1.9 m)	73 in (1.9 m)
Operating weight	6,830 lb (3098 kg)	7,677 lb (3482 kg)	8,830 lb (4005 kg)	8,910 lb (4042 kg)

OPTIONS				
Hydraulic self-leveling	Yes	Yes	Mechanical STD	Yes
Ride control	Yes	Yes	Yes	Yes
High-flow hydraulics	Yes	Yes	Yes	Yes
Air conditioning	Yes	Yes	Yes	Yes
2-speed	Yes	Yes	Yes	Yes

- **Spring applied hydraulic release parking brake for precise and easy operation**
- **Single point daily service for low maintenance cost**
- **Warranties**  
**Base - 1 year; Engine 2 year/2000 hours for maximum confidence and investment protection**





NOTE: All engines meet current EPA emission regulations.

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

IMPORTANT: CNH America LLC reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Availability of some models and equipment builds vary according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your Case dealer/distributor will be able to give you details of the products and their specifications available in your area.



Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

**CNH** CASE IS A BRAND OF CNH,  
A GLOBAL LEADER IN CONSTRUCTION EQUIPMENT, AGRICULTURAL EQUIPMENT AND FINANCIAL SERVICES.

© 2005 CNH America LLC. Case is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. All rights reserved. Printed in U.S.A.